



|   |   |
|---|---|
| Declaration of Performance<br>113-40-2013 | London Mosaic Restoration Ltd, Unit 6, Chiltonian Industrial Estate,<br>Manor Lane, London, SE12 0TX, UK. |
|---|---|

|                           |   |
|---------------------------|---|
| Range<br>Unglazed 10x10cm | Product Category<br>Group Bla<br>EN 14411 : 2012<br>Annex G<br>Dry Pressed Ceramic Tile With Water Absorption Eb < 0.5% (% by mass) |
|---------------------------|---|

|                             |  |
|-----------------------------|--|
| Country of Origin<br>France | Scope / Intended Use<br>Internal Wall      Internal Floor      External Wall      External Floor<br>✓                                  ✓                                  ✓                                  ✓ |
|-----------------------------|--|

| Characteristic                    | Performance                  | Harmonised Technical Specification |
|-----------------------------------|------------------------------|------------------------------------|
| Reaction to Fire                  | Class A1-A1fl                | 96/603/EEC                         |
| Breaking Strength                 | 2816 ± 19 N                  | ISO 10545-4                        |
| - Modulus of Rupture              | 61.8 ± 1.3 N/mm <sup>2</sup> | ISO 10545-4                        |
| Durability                        |                              |                                    |
| - Internal Use                    | Pass                         | EN 14411:2012                      |
| - External Use (Freeze-Thaw)      | Pass                         | ISO 10545-12                       |
| Thermal Shock Resistance          | Pass                         | ISO 10545-9                        |
| Release of Dangerous Substances * |                              |                                    |
| - Lead                            | NPD                          | ISO 10545-15 (Pb)                  |
| - Cadmium                         | NPD                          | ISO 10545-15 (Cd)                  |
| Slip Resistance                   |                              |                                    |
| - Barefoot Ramp Test              | B                            | DIN 51097                          |
| - Shod Ramp Test                  | R10                          | DIN 51130                          |
| - Pendulum Test (Dry)             | 59                           | BS 7976-2:2002                     |
| - Pendulum Test (Wet)             | 39                           | BS 7976-2:2002                     |
| Bonding Strength                  |                              |                                    |
| - Cementitious Adhesive C2        | > 0.5 N/mm <sup>2</sup>      | EN 12004:2007 4.1                  |
| - Dispersive Adhesive D2          | > 1.0 N/mm <sup>2</sup>      | EN 12004:2007 4.2                  |
| Abrasion Resistance               | PEI: V                       | ISO 10545-7                        |
| Chemical Resistance               | Stable                       | ISO 10545-13                       |
| Stain Resistance                  | Pass                         | ISO 10545-14                       |

\* Where values are declared for 'Release of Dangerous Substances', the Notified Body information is given below:  
 NB 1289 : CERAM Research Ltd.  
 89/106/EEC : Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ  
 Test Reference: (132447) - 10499 to (132447) - 10501 17th -31st May 2013

The product outlined herein, identified by "Range", is in conformity with the declared performances in the table above  
 This declaration of performance is issued under the sole responsibility of the manufacturer outlined above